


# NLS-HR1250

## Hand-held Barcode Scanner



### Features

#### ▪ Ergonomic Lightweight Design

This ergonomic lightweight scanner fits **comfortably in any user's** hands to reduce the fatigue of long-time operation, ideally suited for scan-intensive applications.

#### ▪ Cost-effective Solution

The NLS-HR1250 delivers aggressive scanning capabilities and excellent user experiences at an attractive price.

#### ▪ Snappy Scanning Performance

The NLS-HR1250 offers an impressive read rate of up to 300 scans per second, helping boost productivity and profitability.

### Application Scenarios

Retail chains, inventory counting, express delivery services, warehouse management, food traceability, healthcare, manufacturing, electricity meter reading.

# NLS-HR1250

SCANNING MADE SIMPLE

## Hand-held Barcode Scanner

Performance	Image Sensor	Linear imager
	Light Source	Red LED (610nm~640nm)
	Symbologies	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.
	Resolution	≥4mil
	Typical Depth of Field	EAN-13: 50mm-655mm (13mil) Code 39: 55mm-165mm (5mil) Code 128: 40mm-495mm (10mil)
	Scan Angle	Pitch: ±60°, Roll: ±30°, Skew: ±60°
	Min. Symbol Contrast	30%
	Scan Rate	300 scans per second
	Interfaces	USB
	Physical/ Electrical	Dimensions (L×W×H)
	Weight	130g (including USB cable)
	Notification	Beep, LED indicator
	Input Voltage	DC5V
	Current	Maximum Current: <120mA Operating Current: 55mA±5mA Standby Current: 21mA±2mA
Environmental	Operating Temperature	-20°C to 60°C (-4°F to 140°F)
	Storage Temperature	-40°C to 85°C (-40°F to 185°F)
	Humidity	5% ~ 95% (non-condensing)
	ESD	±8 KV (contact discharge); ±10 KV (air discharge)
Certifications		FCC Part15 Class B, CE EMC Class B

\*Specifications are subject to change without notice.\*

Version: V2.0

**Newland China**  
+86-591-83978605  
contact@nlscan.com  
www.newlandaidc.com

**Newland Europe**  
+31(0)-345-87-0033  
info@newland-id.com  
www.newland-id.com

**Newland North America**  
+1-510-490-3888  
info@newlandna.com  
www.newlandamerica.com

**Newland Latin America**  
+1-239-598-0068  
info@newlandla.com  
www.newlandamerica.com

**Newland Taiwan**  
+886-2-7731-5388  
info@newland-id.com.tw  
www.newland-id.com.tw

**Newland Korea**  
+82-10-8990-4838  
th.sung@newland-id.com.tw  
www.newlandaidc.com

